



STRIPING CONSTRUCTION NOTES:

- | | |
|---|---|
| 1. INSTALL 12" CROSS WALK WHITE LINE. | 12. INSTALL LANE DROP LINE (DETAIL 37B). |
| 2. INSTALL LANE LINE (DETAIL 9 & 10). | 13. INSTALL 4" SOLID YELLOW LINE AND YELLOW REFLECTIVE MARKER (DETAIL 25A). |
| 3. INSTALL 50' OF 4" SOLID WHITE LINE. | 14. INSTALL 4" SOLID WHITE EDGE LINE (DETAIL 27B). |
| 4. INSTALL DOUBLE YELLOW LINE (DETAIL 22). | 15. INSTALL SIGN AND POST AS INDICATED (STD. SIZE). |
| 5. INSTALL TYPE IV ARROWS AS SHOWN. | 16. PAINT MEDIAN NOSE IN YELLOW. |
| 6. INSTALL 12" SOLID WHITE LINE AS SHOWN. | 17. INSTALL 4" DASH LINE EXTENSION (DETAIL 40). |
| 7. INSTALL 8" WHITE CHEVRON LINE 25' O.C. UNLESS INDICATED OTHERWISE. | 18. INSTALL TYPE II ARROWS AS SHOWN. |
| 8. INSTALL PAVEMENT MARKING AND MESSAGE AS SHOWN. | 19. INSTALL TYPE III ARROWS AS SHOWN. |
| 9. INSTALL 8" SOLID WHITE LINE (DETAIL 38). | 20. INSTALL TYPE VI ARROWS AS SHOWN. |
| 10. INSTALL 2 SETS OF DOUBLE YELLOW LINE (DETAIL 29). | 21. INSTALL 8" SOLID WHITE LINE (DETAIL 36). |
| 11. INSTALL TWO-WAY LEFT-TURN LANE (DETAIL 32). | 22. INSTALL 12" CROSS WALK YELLOW LINE. |
| | 23. INSTALL TYPE I ARROWS AS SHOWN. |

STRIPING GENERAL NOTES:

- TRAFFIC STRIPES, PAVEMENT LEGENDS, SIGNS AND RAISED PAVEMENT MARKERS PER LATEST EDITION OF CALIFORNIA MUTCD.
- ALL CONFLICTING LINES, LEGENDS, RAISED PAVEMENT MARKERS AND SIGNS SHALL BE REMOVED BY WET SANDBLASTING AND INCLUDES REMOVAL OF RAISED PAVEMENT MARKERS.
- PAVEMENT DAMAGE DUE TO REMOVING RAISED PAVEMENT MARKERS SHALL BE REPAIRED TO THE SATISFACTION OF THE CITY ENGINEER.
- STRIPING SHALL BE CAT TRACKED AND APPROVED BY THE CITY TRAFFIC ENGINEER PRIOR TO FINAL INSTALLATION. MINIMUM OF ONE WEEK NOTICE REQUIRED BY THE CITY TRAFFIC ENGINEER FOR APPROVAL OF STRIPING.
- ALL STRIPING SHALL BE THERMOPLASTIC UNLESS OTHERWISE NOTED.
- ALL LANE LINES AT INTERSECTION APPROACHES AND DEPARTURES SHALL BEGIN AND END WITH 50 FEET OF 4-INCH SOLID WHITE LANE.
- LANE WIDTH SHALL BE MEASURED BETWEEN THE CENTER LINES OF EACH ADJACENT SINGLE OR DOUBLE STRIPE OR TOP OF CURB AS APPROPRIATE.
- ALL SIGNS ARE TO BE REFLECTORIZED USING 3-M DIAMOND GRADE SHEETING (TYPE 11 WITH 1160A GRAFFITI OVERLAY).
- ALL SIGNS ARE TO BE STANDARD SIZE AND PER STATE OF CALIFORNIA SIGN SPECIFICATIONS EXCEPT THAT ALL SIGNS SHALL BE MINIMUM .01 INCH THICK ALUMINUM SHEETING.
- ALL SALVAGED SIGNS AND POSTS SHALL BE DELIVERED TO THE CITY MAINTENANCE YARD UNLESS OTHERWISE INDICATED.
- CALTRANS TRAFFIC MANUAL, STANDARD PLANS AND STANDARD SPECIFICATIONS, ENGLISH UNITS EQUIVALENT.
- ALL CURB MARKINGS (RED, BLUE, ETC.) SHALL BE REFRESHED WITHIN PROJECT LIMITS.
- INSTALL BLUE RAISED PAVEMENT MARKERS IN FRONT OF THE HYDRANTS.
- ALL ARROW MARKINGS SHALL BE TYPE IV (L OR R) UNLESS OTHERWISE NOTED.
- ALL NEW SIGN POST SHALL BE UNI-STRUT.

MATCHLINE AT STA. 12+19.92
SEE SHEET 17 A

REVISIONS					DATE	BY	APP.

CITY OF HAWTHORNE
DEPARTMENT OF PUBLIC WORKS ENGINEERING DIVISION

ROSECRANS AVENUE IMPROVEMENT
STRIPING AND SIGNAGE PLAN - ROSECRANS AVE. STA. 6+96.27 TO 12+70

CONSTRUCTION RECORD	F. B. REF.	DATE	STAMP:	APPROVED BY:
DATE STARTED	DESIGNED BY	A.L. 5/16/2011		
DATE COMPLETED	DRAWN BY	J.V. 5/16/2011		
	CHECKED BY			

ARNOLD SHADBEHR	C48554
CITY ENGINEER	R.C.E. NO.

SCALE: 1"=40' SHT. 17 OF 27 DWG. NO.

K:\Engineering\2011\05\Rosecrans\Scale Plans\ROSECRANS STRIPING.dwg